




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06F 3/147	A2	(11) International Publication Number: WO 99/18495 (43) International Publication Date: 15 April 1999 (15.04.99)
(21) International Application Number: PCT/SE98/01763 (22) International Filing Date: 30 September 1998 (30.09.98) (30) Priority Data: 9703589-3 2 October 1997 (02.10.97) SE (71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON [SE/SE]; S-126 25 Stockholm (SE). (72) Inventor: HEDBERG, Anders; Kämnärvägen 7G-206, S-226 46 Lund (SE). (74) Agents: STRÖM, Tore et al.; Ström & Gulliksson AB, P.O. Box 4188, S-203 13 Malmö (SE).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>

(54) Title: A HAND-HELD DISPLAY DEVICE AND A METHOD OF DISPLAYING SCREEN IMAGES



(57) Abstract

In a hand-held display device (1) for use with an electronic device (13) to display a complete or a determined part (8) of a screen image (7), there are included control circuits, a display screen (2) and control buttons (3) connected to said control circuits. Further, a gyroscope (6) is incorporated in said display device (1) and connected to said control circuits, whereby said display device (1) is responsive to movements in the space for displaying said screen image (7) in different magnifications, and/or in different parts (8).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

TITLE: **A HAND-HELD DISPLAY DEVICE AND A
METHOD OF DISPLAYING SCREEN
IMAGES**

Field of the Invention

The present invention relates to a hand-held display
10 device and a method for its use with an electronic device
to display a complete or a determined part of a screen
image.

Description of the Prior Art

15 Several electronic devices, such as a mobile tele-
phone, a PDA (Personal Digital Assistant), an organizer, or
a PC (personal computer) etc. are provided with a display
or a monitor for displaying different kind of information.
A typical personal computer system, notebook, or hand-held
20 computer consists of a system unit, storage means, a
display, keyboard and a mouse or other interactive input
devices such as a digitizing tablet, joystick, lightpen
etc. to control the computer.

The primary attributes of a display is the size of
25 the display screen; the resolution of the display; and
whether the display is monochrome or in colour. The size of
a display screen can vary from, for example, 5 to 25 inches
in diagonal dimension. The quality of output or the resolu-
tion of a common display or monitor is for example 640x480,
30 800x600, or 1024x768 pixels.

There is a variety of displays available from differ-
ent vendors. These displays are designed to accomplish par-
ticular functions. An engineer needs a large high-resolu-
tion monitor for CAD-applications and a smaller monochrome
35 monitor for the display of text and graphic information. A
full-page colour monitor can be utilized for both landscape
and portrait presentations. Also, hand-held data entry de-
vices or computers are provided with a small display. A

common hand-held data entry device has a limited keyboard and some kind of storage capability for the data. Another hand-held data entry device combines a hand-held optical wand with a keyboard. Stock clerks use such devices in
5 stores to collect and enter reorder data.

For some purposes small flat-panels are required to save space. Flat-panels are used in conjunction with small size electronic devices such as notebooks, hand-held computers, mobile telephones etc.

10 Many vendors offer or are just about to offer hand-held computers. These computers are provided with flat-panels having for example a 640x240 resolution touchscreen, or 480x240 resolution touchscreen. Such panels or display screens cannot be too limited in size and resolution to be
15 useful for their intended purpose, i.e. to present general software applications such as word processing, desktop publishing, spreadsheet, databases, internet applications etc. The limitations are set in view of the sight properties of a human being.

20 Consequently, a problem associated with prior art computer configurations is that access is needed to several types of computers provided with different displays suitable for different kinds of applications. As described above, a very small sized flat-panel of a hand-held data
25 entry device, a mobile telephone, or a computer etc. is not at the same time capable of display full-screen documents in a proper and readable way.

JP-A-7 234 664 discloses a document image display, which reads out the contents of a document using a scanner
30 and the image of the document is stored in a page memory. An area of the document specified by an operator is read from the memory and then magnified. The magnified area, stored in a working memory, is then displayed on an operation display.

Summary of the Invention

The present invention is directed to an improved display device for use with an electronic device, which overcomes one or more of the limitations and disadvantages of the related art.

It is an object of the present invention to provide a hand-held display device for use with an electronic device, said display device being suitable for the purpose of a hand-held data entry device as well as for both landscape and portrait presentations of a full-page word processing document. Further, it can satisfy the needs of an engineer working with CAD-applications as well as for the display of text and graphic information. Also, hand-held computers can be provided with a display device of the present invention.

Consequently, another object of the present invention is to provide a hand-held display device for use with a computer to display a complete or a determined part of a screen image in a proper size with regard to the current needs or requirements of a user.

Still another object of the invention is to provide a display device incorporated in an electronic device such as a mobile telephone, a PDA (Personal Digital Assistant), an organizer, a data terminal to display a complete or a determined part of a screen image in a proper size with regard to the current needs or requirements of a user.

These objects are accomplished by a display device having movement sensitive means such as a micro gyroscope, strain gauge, piezo-electric, or equilibrium of force accelerometer etc incorporated in said display device, thereby being responsive to movements in the space for displaying the complete screen image in different magnifications, or in different parts.

Further, a method of displaying a complete or a determined part of a screen image in a proper size with regard to the current needs or requirements of a user is also

provide by the invention, wherein said display device is activated by pressing an activation control button of said display device, and said display device is moved essentially in the plane of said display device, whereby different parts of a complete screen image are shown on said display screen, and/or said display device is moved essentially in a direction perpendicular to the plane of said display device, whereby the magnification of said screen image is changing.

10

Brief Description of the Drawings

In order to explain the invention in more detail and the advantages and features of the invention a preferred embodiment will be described in detail below, reference being made to the accompanying drawings, in which

15

FIG 1 is a front view of a display device according to one embodiment of the present invention, showing a cutting of a complete screen image,

FIG 2 is a schematical view of the complete screen image including the cutting in FIG 1, on a conventional CRT-device with a superimposed virtual display device according to the present invention,

20

FIG 3 is a view of a computer configuration provided with the display device according to the invention, operated by a user,

25

FIG 4 is a front view of the display device of FIG 1, showing the complete screen image of FIG 2 in a compressed shape, and

FIG 5 is a front view of a mobile telephone provided with a display device according to the invention.

30

Detailed Description of the Invention

A display device 1 according to the present invention for use with an electronic device such as a mobile telephone, a PDA (Personal Digital Assistant), an organizer, a

35

data terminal or a computer to display a complete or a determined part of a screen image is shown in FIG 1. Said display device is provided with control circuits, not shown in FIG 1. A display screen 2 and control buttons 3, such as touch control buttons, are incorporated in said display device 1 and connected to said control circuits. For connection with a computer or a network connection means 4, for example an IR (infra red) or radio transmitter/receiver, or a connection cable etc. is attached to the display device.

10 Movement sensitive means 6 comprising a micro gyroscope, strain gauge, piezo-electric, or equilibrium of force accelerometer etc is incorporated in said display device 1 and connected to said control circuits, said display device being responsive to movements in the space for displaying the complete screen image in different magnifications, and/or different parts of a screen image.

Power supply for the display device is provided by for example local batteries, sunlight power, kinetic energy, or the power supply of an attached computer.

20 One of said control buttons 3 is an activation control button provided for activation of said display device 1 to be responsive for movements. Thus, said display device 1 is activated by pressing said activation control button 3, and then by moving said display device 1 essentially in the plane of said display device, different parts of a screen image are shown on the display screen 2.

30 This is schematically illustrated in FIG 2, wherein a cutting 8, corresponding to the image shown on the display screen 2 in FIG 1, is surrounded by a superimposed dashed virtual display device 9 corresponding to the size of the display device 1. When said virtual display device 9 is moved around on said screen image 7, different cuttings 8 are covered. Correspondingly, these cuttings 8 are displayed when the real display device 1 is moved in the plane of said display device.

35

As shown in FIG 3, a user 10 is moving said display device up and down, illustrated by an arrow 11, and to the left and right, illustrated by an arrow 12, to present different parts of the screen image 7. In a particular position in the space the cutting 8 of the screen image 7 is presented on the display screen 2. Hence, it is possible for the user of the display device 1 to read text that does not actually fit into the small display screen 2, by moving the display device a short distance in space in the plane of said display device.

By activation of said display device 1 by pressing said activation control button 3 and then moving said display device back and forth, essentially in a direction perpendicular to the plane of said display device, illustrated by an arrow 14, the magnification of said screen image 7 is changed or the image is zoomed. As shown in FIG 3 and in more detail in FIG 4, it is possible to zoom out as much as an overview of the complete screen image 7 is shown on the display device 1.

It should be apparent that the present invention provides an improved display device 1 and a method for use with an electronic device such as a computer 13 to display a complete or a determined part of a screen image 7 by moving said display device 1 in the space, wherein different parts of the screen image 7 are shown in different magnifications on said display screen 2. Although the invention has been described in conjunction with a specific embodiment thereof, this invention is susceptible of embodiments in different forms, with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the invention to the specific embodiment illustrated.

For example, in another embodiment of the invention the different parts: display screen, movement sensitive

means, control buttons, electronic circuits and/or connection means, of said display device can be incorporated as a single unit or as separate parts in an electronic device such as a mobile telephone, a PDA
5 (Personal Digital Assistant), an organizer, data terminal, or a hand-held computer, wherein the operations described above are performed in a similar manner. Consequently, the conventional keypad of the particular electronic device may comprise control buttons for the display functions of the
10 invention. Further, these kinds of electronic devices, provided with a display device of the invention, can work as stand alone devices with no need for connection means, as well as devices having a connection with another electronic device or network.

15 In a particular embodiment of the invention said display device is incorporated in a mobile telephone unit providing both computer and telephone facilities, shown in FIG 5. The conventional transmitter/receiver units of the mobile telephone may be utilized as connection means for
20 connection with other electronic devices or networks.

Different kinds of technologies can be utilized for the display screen 2, such as LCD (liquid crystal display), gas plasma, EL (electroluminescent), TFT (thin film transistor) etc.



CLAIMS

1. A hand-held display device (1) for use with an electronic device (13) to display a complete or a determined part of a screen image (7), provided with control circuits, a display screen (2) and control buttons (3) connected to said control circuits, characterized by movement sensitive means (6) incorporated in said display device (1) and connected to said control circuits, whereby said display device (1) is responsive to movements in the space for displaying said screen image (7) in different magnifications, and/or in different parts (8).
2. A display device according to claim 1, characterized by movement sensitive means (6) comprising a micro gyroscope, strain gauge, piezo-electric, or equilibrium of force accelerometer.
3. A display device according to claim 1 or 2, characterized by connection means (4) for connection with an electronic device (13) or a network.
4. A display device according to claim 3, characterized in that said connection means (4) is a light or radio transmitter/receiver, or a connection cable.
5. A display device according to any of the preceding claims, characterized by being incorporated in a mobile telephone, a PDA (Personal Digital Assistant), an organizer, data terminal, or a hand-held computer.
6. A display device according to any of the preceding claims, characterized by an activation control button (3) provided for activation of said display device (1) to be responsive for movements.

7. A display device according to any of the preceding claims, c h a r a c t e r i z e d in that said display screen (2) is an LCD-display, a gas plasma display, an EL
5 (electroluminescent) display, or a TFT (thin film transistor) display.

8. A method of displaying a complete or a determined part (8) of a screen image (7) provided by a an electronic
10 device (13) connected to a hand-held display device (1) according to any of the preceding claims, c h a r a c t e r i z e d by the steps of
activating said display device (1);
moving said display device (1) essentially in the
15 plane (11,12) of said display device (1), whereby different parts (8) of a complete screen image (7) are shown on said display screen (2); and/or
moving said display device (1) essentially in a direction (14) perpendicular to the plane of said display device (1), whereby the magnification of said screen image
20 (7) is changing (FIG 3).

1/3



2/3




FIG. 3




FIG. 4

3/3




FIG. 5